





MOTOR WITH PTC THERMAL PROTECTION blue-blue 130°C

Power [kW] 1.1	Duty Cycle S1	Base speed [rpm] 18000	Base freq. [Hz] 300	Base voltage Δ [V] 220	Base voltage Y [V] 380	Protection IP54	Ins. Cl. F	
Min speed [rpm] 3000		Max speed [rpm] 24000	Max freq. [Hz] 400	Absorb. Δ [A] 5.0	Absorb. Y [A] 2.9	Part number on nameplate COM41470576		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		full type 	half type 	Peso / weight 6.72 kg		Teknomotor S.r.l. Via Argenege 31, I-32038 Quero Vas (BL) www.teknomotor.com
Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	
rev. n° 00	description Emissione			date 23/02/2017	signature D. Bottarel	Customer Catalogo		
						Drawing code COM41470576		
drawn - date D. Bottarel - 23/02/2017	approved - date S. Perli - 23/02/2017	checked - date S. Perli - 23/02/2017	sostituisce il sostituito dal		foglio / sheet 1 / 1	scala 1:2		A4